




**MUCCO**  
WARNING LAMPS

SNT-U125-DT2-22  
85-260V AC/DC

CE EMC RoHS2 ISO9001 IP65



Stack Lights




RGB Warning Lights



Signal Beacons



LED Warning Horns



Beacon Horns



Electronic Sirens





SMD LED  
Super Bright

Impact Resistant  
Polycarbonate Lens

ABS Housing  
IP65 Protection  
Rate



- Mucco Low-intensity B type obstruction lights are manufactured according to ICAO (ANNEX 14) standards. All lighting systems have an IP65 protection class and are guaranteed for 2 years.
- By perceiving the level of light becomes active in the dark, becomes deactive in the daylight.
- It does not take account of the temporary loss of light throughout 30 sec. and It abolishes the light illusion.
- It gives a normally open, normally closed relay output over 30% in light loss and power failure.
- It has a 360-degree view range from 10 km.



## OBSTRUCTION LIGHTS

Obstruction lights are vital in making high-rise buildings, towers and wind turbines visible to passing aircraft.

- Lens: Polycarbonate
- Lens Diameter: 100mm, 125mm
- LED Module: SMD
- LED life duration: 50.000 hrs
- Light Colors: Red, Green, Yellow
- Light Modes: Steady, Flashing
- Housing: ABS, Metal
- Mounting Types: Surface & Wall
- Does not affected by water, dust, heat and UV rays
- Warranty: 2 Years

- Compliant with Annex 14 ICAO standards.
- Activates in the dark and deactivated in the light by detecting the light level.
- It ignores the temporary light source for 30sec and eliminates the light illusion.
- Normally open, normally closed relay output in a condition of over %30 light loss and power cut.
- Visibility distance: 10km
- Visibility degree: 360
- Wireless option with solar energy.

### Voltage Options:






- Option 1: 12V/DC
- Option 2: 24V/DC
- Option 3: 48V/DC
- Option 4: 85-260V/AC

### For more Details

Scan the QR Code for more information about the product



- Before making electrical connections to the products, please read the user manuals included in the box!
- Do not energize signal and contact cables other than the power cable (2x0.50mm).
- The product is out of warranty when the signal and contact cables are energized.
- The connection of the product should be made by at least electric technicians.







Stack Lights



RGB Warning Lights



Signal Beacons



LED Warning Horns



Beacon Horns



Electronic Sirens



## 100 Obstruction Light

Lens Diameter: 100mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: ABS  
Mounting Types: Surface & Wall



### Voltage Options:

Option 1: 12V/DC  
Option 2: 24V/DC  
Option 3: 48V/DC  
Option 4: 85-260V/AC

### Part no.

### Light Mode

SNT-U100-...	Flashing
SNT-U100S-...	Steady



## 125 Obstruction Light

Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: ABS  
Mounting Types: Surface & Wall



### Voltage Options:

Option 1: 12V/DC  
Option 2: 24V/DC  
Option 3: 48V/DC  
Option 4: 85-260V/AC

### Part no.

### Light Mode

SNT-U125-...	Flashing
SNT-U125S-...	Steady



## Base Mount Obstruction

Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: Metal  
Mounting Types: Surface



### Voltage Options:





Option 1: 12V/DC  
Option 2: 24V/DC  
Option 3: 48V/DC  
Option 4: 85-260V/AC

### Part no.

### Light Mode

SNT-U125-DTI-...	Flashing
SNT-U125-SDTI-...	Steady






## Single Arm Obstruction Light

Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: Metal  
Mounting Types: Wall

### Voltage Options:

Option 1: 12V/DC  
Option 2: 24V/DC  
Option 3: 48V/DC  
Option 4: 85-260V/AC

Part no.	Light Mode
SNT-U125-D1-...	Flashing
SNT-U125-SD1-...	Steady



## Dual Arm Obstruction Light

Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: Metal  
Mounting Types: Surface


### Voltage Options:

Option 1: 12V/DC  
Option 2: 24V/DC  
Option 3: 48V/DC  
Option 4: 85-260V/AC

Part no.	Light Mode
SNT-U125-DT2-...	Flashing
SNT-U125-SDT2-...	Steady



A Single Lamp Operates in the Dual Obstruction Lights. At a %30 Light Loss or Damage, the Other Lamp Automatically Switches On



## Base Mount Solar Obstruction Light




Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: ABS/ Metal  
Mounting Types: Surface

### Power Supply: Solar Energy

### 20W Solar Panel Obstruction Light.

Part no.	Light Mode
SNT-U125-SLT25	Flashing
SNT-U125-SSLT25	Steady





### Wall Mount Solar Obstruction Light

- The product must be kept in a closed position when it is in the box or in unused areas. (Overdischarge of the battery causes the battery not to be recharged.)
- In order to for the product to be automatically activated, the switch located on top of the product must be in position "on". Product activates only when it gets dark.
- Ensure that the solar panel on the product has the best contact with the sun.


Lens Diameter: 125mm  
Light Colors: Red  
Light Modes: Steady, Flashing  
Housing: Metal  
Mounting Types: Wall

Part no.	Light Mode
SNT-U125-SL25	Flashing
SNT-U125-SSL25	Steady

**20W Solar Panel Obstruction Light.**








Stack Lights




RGB Warning Lights




Signal Beacons



LED Warning Horns



Beacon Horns



Electronic Sirens



## 100 Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U100-12	ø100	Flashing	12V/DC	80USD
SNT-U100-24	ø100	Flashing	24V/DC	80USD
SNT-U100-48	ø100	Flashing	48V/DC	80USD
SNT-U100-22	ø100	Flashing	85-260V/DC	80USD
SNT-U100S-12	ø100	Steady	12V/DC	80USD
SNT-U100S-24	ø100	Steady	24V/DC	80USD
SNT-U100S-48	ø100	Steady	48V/DC	80USD
SNT-U100S-22	ø100	Steady	85-260V/DC	80USD




## 125 Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-12	ø125	Flashing	12V/DC	80USD
SNT-U125-24	ø125	Flashing	24V/DC	80USD
SNT-U125-48	ø125	Flashing	48V/DC	80USD
SNT-U125-22	ø125	Flashing	85-260V/DC	80USD
SNT-U125S-12	ø125	Steady	12V/DC	80USD
SNT-U125S-24	ø125	Steady	24V/DC	80USD
SNT-U125S-48	ø125	Steady	48V/DC	80USD
SNT-U125S-22	ø125	Steady	85-260V/DC	80USD



## Base Mount Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-DTI-12	ø125	Flashing	12V/DC	95USD
SNT-U125-DTI-24	ø125	Flashing	24V/DC	95USD
SNT-U125-DTI-48	ø125	Flashing	48V/DC	95USD
SNT-U125-DTI-22	ø125	Flashing	85-260V/DC	95USD
SNT-U125-SDTI-12	ø125	Steady	12V/DC	95USD
SNT-U125-SDTI-24	ø125	Steady	24V/DC	95USD
SNT-U125-SDTI-48	ø125	Steady	48V/DC	95USD
SNT-U125-SDTI-22	ø125	Steady	85-260V/DC	95USD



## Single Arm Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-D1-12	ø125	Flashing	12V/DC	95USD
SNT-U125-D1-24	ø125	Flashing	24V/DC	95USD
SNT-U125-D1-48	ø125	Flashing	48V/DC	95USD
SNT-U125-D1-22	ø125	Flashing	85-260V/DC	95USD
SNT-U125-SD1-12	ø125	Steady	12V/DC	95USD
SNT-U125-SD1-24	ø125	Steady	24V/DC	95USD
SNT-U125-SD1-48	ø125	Steady	48V/DC	95USD
SNT-U125-SD1-22	ø125	Steady	85-260V/DC	95USD



## Dual Arm Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-DT2-12	ø125	Flashing	12V/DC	235USD
SNT-U125-DT2-24	ø125	Flashing	24V/DC	235USD
SNT-U125-DT2-48	ø125	Flashing	48V/DC	235USD
SNT-U125-DT2-22	ø125	Flashing	85-260V/DC	235USD
SNT-U125-SDT2-12	ø125	Steady	12V/DC	235USD
SNT-U125-SDT2-24	ø125	Steady	24V/DC	235USD
SNT-U125-SDT2-48	ø125	Steady	48V/DC	235USD
SNT-U125-SDT2-22	ø125	Steady	85-260V/DC	235USD



## Base Mount Solar Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-SLT25	ø125	Flashing	Solar Energy	450USD
SNT-U125-SSLT25	ø125	Steady	Solar Energy	450USD



## Wall Mount Solar Obstruction Light

PART NO	LENS DIA.	TYPE	POWER SUPPLY	PRICE
SNT-U125-SL25	ø125	Flashing	Solar Energy	500USD
SNT-U125-SSL25	ø125	Steady	Solar Energy	500USD



## Mounting Parts

PART NO	TYPE	CATEGORY	COLOR	PRICE
SNT-125LNK	ø125 PC-Lens	Obstruction Light	Red	12USD
SNT-125L	Metal Wall Bracket	Obstruction Light	Gray	25USD
SNT-125TB	Metal Surface Bracket	Obstruction Light	Gray	25USD